Rev - 1 Rev - 2 -10'-0 1/2**"---**-36 1/2" -32 1/2" - | 18 1/4" POWER REQUIREMENTS 117 V.A.C. 60 HZ 18 AMP WITH HEATER OPTION 4 AMP WITHOUT HEATER OPTION 10 3/4" • 38 1/2" INTERIOR FLOOR LEVEL DRIVEWAY LEVEL MASONRY OPENING - INTERIOR DETAIL THE EXTENSION OF THE BUCKET CAN BE ADJUSTED FROM 9" MINIMUM TO 17 1/2" MAXIMUM. (COMES SET @ 17 1/2" FROM FACTORY) 10'-3" -10'-4 17/32**'**to 13" STD. 37 3/4" 38 3/16" r 1 1/2" — HEATER OPEŅONG COVER 10 1/24 11 1/4" (WINDOW FRAME OVERLAPS DEAL DRAWER 1/4") - 32" WINDOW FRAME IF NOT NOTCHED. DRAWER MAY BE LOCATED ANYWHERE UNDER WINDOW... -WHERE OPTIONAL 117 VAC 20 AMP DUPLEX DUTLET HEATER WOULD BE INSTALLED.... EXTERIOR ELEVATION INTERIOR ELEVATION 10" MAXIMUM WALL THICKNESS TO ACCOMMODATE 19' DEEP UNDERCOUNTER STEEL CABINETS. VERTICAL SECTION HAMILTON SAFE 310D WINDOW WITH

400DD DEAL DRAWER
U.L. LISTED

Drawing Number: 95-696 | Date: 5-18-99